

FRD remote displays



product description

The FRD family of remote displays comprises of five versions for use in various weighing systems within the weighing machines and process weighing sectors. The displays have environmental protection rated at IP65 or IP67.

The FR-57, FRD-57B and the FRD-100B are stainless steel housed devices for wall mounting – with red LED display.

The FRD-55 and FRD-100 wall mount displays offer brighter LED display for use in well-lit environments. Ideal for outdoor use.

key features

6 digit displays

Wall mounted enclosures

Steel or aluminium housings

55mm, 57mm and 100mm display height versions available

Serial interface – RS232/RS485



RoHS
compliant



specifications

| Model | FRD-57 | FRD-55 LED | FRD-100 LED | FRD-57B | FRD-100B |
|---------------------|--|--|-------------|----------------------------------|----------|
| Display technology | LED red | LED super red, suitable in sunlight environments | | | |
| Display height (mm) | 57 | 55 | 100 | 57 | 100 |
| Display | 6 digits, 7 segments | | 6 digits | | |
| Weight display | +/- sign and 5 digits, decimal point between any digit | | | Indication for zero, net, stable | |
| Designator | Permanent label sticker | | | - | - |
| Other | - | Automatic lightness control; 140° reading angle | | Sun shield | |

Communication

| | | | |
|------------------|---|-------------------------------------|---|
| Serial interface | RS-232, RS-485 and 20 mA TTY current loop; field selectable | RS-232 and RS-485; field selectable | RS-232, RS-485 and 20 mA TTY current loop |
|------------------|---|-------------------------------------|---|

Power

| | | | | |
|--------------------|----------------------------------|---------------------------|---------------------------|----------------------------------|
| Power requirements | 230V AC ±20%, 50...60Hz, max. 7W | 190...240V AC, max. 350mA | 190...240V AC, max. 500mA | 100...240V AC or 24V DC (option) |
|--------------------|----------------------------------|---------------------------|---------------------------|----------------------------------|

Environment and enclosure

| | | | | | |
|-----------------------|-----------------------------|----------------------|----------------|-----------------|----------------|
| Operating temperature | -20°C to +50°C | -20°C to +60°C | -15°C to +55°C | | |
| Storage temperature | -10°C to +70°C | -20°C to +60°C | - | | |
| Humidity | 90% RH max., non-condensing | | | | |
| Enclosure | Stainless steel | Aluminium, 3mm thick | | Stainless steel | |
| Protection | IP65 | | | IP67 | |
| Dimensions (mm) | 445 x 202 x 72 | 480 x 150 x 60 | 630 x 150 x 60 | 467 x 182 x 70 | 700 x 200 x 80 |
| Weight | 3kg | 2.7kg | 3.2kg | 6.5kg | 9.6kg |

Dimensions and specifications are subject to change without notice.